Environmental Data Sheet

ECOSYS MA6000ifx

Environmental Management	This device is manufactured in production facilities that work with an environmental management system in accordance with ISO 14001.		
Power Consumption Heat Emission	Maximum (at switch of Printing: Ready: Low power mode: Sleep-mode: Off-mode:	1309 W 4712 kJ/h 740.8 W 2667 kJ/h 57.9 W 208.4 kJ/h 38.0 W 136.8 kJ/h 0.5 W 1.8 kJ/h 0.1 W 0.4 kJ/h	
Typical Power Consumption (TEC) (According to ENERGY STAR 3.0)	0.84 kWh/week (8960	o pages/week)	
Installation Notes	The unit should be placed in a way, that there is adequately space for operation and maintenance on both sides, as well as in front and behind the system. Provide adequate ventilation. Do not set up the unit in dusty rooms, and protect against ammonia vapours. Please follow the instructions in the user manual.		
Humidity	15% - 80%		
Room Temperature	10°C - 32.5°C		
Noise Emission (According to ISO 7779 / ISO 9296)	[dB(A) L _{pA}] Operator position [dB(A) L _{pA}] Declared A-weighed so [dB(A) L _{WAc}]	Operation Ready Quiet-Morre level distance, average of single measurements 56.0 22.7 50.9 62.0 27.6 56.0 ound power level according to DE-UZ 219 72.5 ound power level following DE-UZ 219 39.2	5)
Light Source	Exposure drum: Laser	1	
Emissions	According to DE-UZ 2 TVOC (Operation): TVOC (Ready): Benzene: Styrene: Ozone: Dust:	7.57 mg/h 0.196 mg/h < limit of detection 0.10 mg/h 0.24 mg/h < limit of quantitation	
ECOlabel	Exposure drum: Laser Product related environmental labels in Germany/Austria/Italy: Blue Angel DE-UZ 219 Status: Awarded List of certified KYOCERA products can be found here: https://www.blauer-engel.de/en/products/brands/kyocera Other countries: Please refer to the local country information.		

effective 05/2023 – Errors and omissions excepted

